3650
INSULATED SANDWICH

doorLink Manufacturing, Inc.®

3 LAYER
SANDWICH CONSTRUCTION

FLUSH PANEL

3650

PAINT	EFFICIENCY
1.0 MIL	10.25 R-VALUE

INTERIOR
STEEL SKIN

2" thick insulated steel sandwich panel constructed of top quality materials. Flush panel with deep woodgrain texture and two coat prefinished paint system all combine to enhance the beauty of your home.

Configure your door on our website at www.DoorLinkMfg.com

3650
INSULATED SANDWICH

3 LAYER
SANDWICH CONSTRUCTION

FLUSH PANEL

STANDARD FEATURES

26 GAUGE METAL
Hot dipped galvanized steel construction provides superior strength and durability.

1.0 MIL PAINT SYSTEM
Includes .25 mil rust inhibiting primer and .75 mil exterior top coat that resists fading and chalking while providing consistent color from panel to panel, and long life.

20 GAUGE HOT DIPPED STEEL HINGE PLATES
Galvanized steel hinge plates run the full height of each section at all hinge locations to facilitate the attachment of hinges, handles, struts and step plates.

TONGUE AND GROOVE MEETING RAILS
For superior strength and better sealing against wind, rain and snow.

RIGID ALUMINUM RETAINER
Provides added strength while securing replaceable u-shaped bottom weatherstrip to help keep the elements out.

R VALUE 10.25 INSULATION
Sandwich type construction with polystyrene insulation pressure bonded between two sheets of 26 gauge hot dipped galvanized steel enhances your home's energy savings, makes your door operation quieter, and reduces exterior noise in your garage.

CFC FREE EXPANDED POLYSTYRENE
Environmentally friendly insulation that will not degrade with vibration or time.

SIZES AVAILABLE

DOOR WIDTH

8', 9', 10', 12', 14', 15', 16', 17', 18', 20', 22', 24'

HEIGHTS AVAILABLE:

6'6" 6'9" 7'0" 7'6" 7'9" 8'0"

COLORS

BROCHURE COLOR MAY VARY FROM ACTUAL PRODUCT.

CONSTRUCTION

PAINT LAYERS

Your Local Authorized Dealer:

doorLink Manufacturing, Inc.®

To view this product online:

IDA International Door Association

DASMA

1501 Taney Street, North Kansas City, MO 64116 **Ph: 816-474-3900** Fax: 816-474-3902

www.DoorLinkMfg.com

© 2015 doorLink Manufacturing, Inc